



**HAL**  
open science

## **Decodable anticipation from prestimulus activity**

Isabelle Hoxha, Sylvain Chevallier, Arnaud Delorme, Arnaud Boutin, Michel Ange Amorim

► **To cite this version:**

Isabelle Hoxha, Sylvain Chevallier, Arnaud Delorme, Arnaud Boutin, Michel Ange Amorim. Decodable anticipation from prestimulus activity. 3rd Neuroergonomics Conference, Sep 2021, Munich (online), Germany. hal-03446751

**HAL Id: hal-03446751**

**https:**

**//hal-universite-paris-saclay.archives-ouvertes.fr/hal-03446751**

Submitted on 24 Nov 2021

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



## Decoding anticipation from prestimulus activity




PRESENTER:

Isabelle Hoxha

**BACKGROUND:** Correctly anticipating stimuli allows for faster responses. While common, perceptual anticipation is difficult to observe in the laboratory as its processes are mainly unconscious (Barik et al., 2019). In particular, asking participants to report anticipation implies the elucidation of unconscious processes, which is a form of decision-making and thus changes brain activity (Koch and Preuschoff, 2007). However, reaction times are helpful to infer the class of anticipation (Petro et al., 2019). While previous EEG studies have shown the impact of prestimulus alpha power (8-13Hz) on performance (Lou et al., 2014), its predictive power has to be assessed for further brain-computer interface applications.


### METHODS

1. 9 healthy adult participants
2. EEG: 32 electrodes, 1000Hz sampling
3. Discrimination task: stimulus is either an image of a face or an image of a number accompanied by a sound



4. Obtain class of anticipation: invert stimulus labels of the trials with response time on the top 25%
5. Alpha power in prestimulus period (Multitaper)
6. Competition between auditory and visual information: ratio of occipital and temporal power: two features (T7/Oz and T8/Oz)
7. SVM classification, 5-fold cross-validation. Compare classification performance with the stimulus labels and with the inverted labels

# Anticipation can be decoded from pre-stimulus alpha power




Permutation testing: shuffle labels on train set, recompute the hyperparameters, test performance on the same test set. 1000 iterations.

- Broad uncertainty on chance level: more iterations needed
- 2 participants show significant classification performance on inverted labels, none on stimulus labels

### About the paradigm...

- Equiprobable stimuli at each trial
- 480 trials



### References:

- Barik, K., et al. (2019). A machine learning approach to predict perceptual decisions: an insight into face pareidolia. *Brain Inf.* 6, 2.
- Koch, C., and Preuschoff, K. (2007). Betting the house on consciousness. *Nat Neurosci* 10, 140-141.
- Lou, B., et al. (2014). Prestimulus alpha power predicts fidelity of sensory encoding in perceptual decision making. *NeuroImage* 87, 242-251.
- Petro, N. M., et al. (2019). Pre-target alpha power predicts the speed of cued target discrimination. *NeuroImage* 189, 878-885.

**Hoxha, Isabelle** (1,2,3,4);  
**Chevallier, Sylvain** (3);  
**Delorme, Arnaud** (4);  
**Boutin, Arnaud** (1,2);  
**Amorim, Michel-Ange** (1,2)

- 1: CIAMS, Université Paris-Saclay, Orsay, France;  
2: CIAMS, Université d'Orléans, Orléans, France;  
3: LISV, UVSQ, Université Paris-Saclay, Vélizy, France;  
4: CerCo, CNRS, Université Toulouse III, Toulouse, France

@Hoxhaisabelle, @sylvcheva,  
@arnodelorme, @ArnaudBoutin8